

Pulse Blow Series Long-Life Type

Twice the durability of the conventional model!

※Based on KOGANEI test conditions.

※Actual durability varies depending on operating conditions and the operating environment.



Pulse Blow Air Gun PAG Series

Pulse Blow Unit PAU Series

⚠ Caution

※ Be sure to read the "Safety Precautions" in the General Catalog or on our website before using this product.

- This catalog is current as of April 2025.
- Specifications and appearance are subject to change without prior notice for product improvement. Please refer to our website for the latest information.



KOGANEI CORPORATION

□ OVERSEAS GROUP
PMO Takanawa Gateway, 2-19-17, Takanawa
Minato-ku, Tokyo, 108-0074, Japan
TEL: (+81)-3-6721-7478

URL <https://www.koganei.co.jp>

Note The external dimensions and available options are identical to those of the standard PAG and PAU Series.
For specifications, dimensional drawings, additional parts, operating principles, frequency adjustment procedures, frequency characteristics, flow characteristics, piping requirements, and handling precautions, please refer to the KOGANEI website or the standard product catalog.

Long-Life Type

Pulse Blow Air Gun PAG Series

Order Codes

PAGL - ☐

Nozzle Diameter

- N** : No nozzle
2 : ϕ 2mm [0.079 in.] Standard Nozzle
3 : ϕ 3mm [0.118 in.] Standard Nozzle
4 : ϕ 4mm [0.157 in.] Standard Nozzle



Secondary-side Mounting Type Pulse Blow Unit PAUS Series

Order Codes

PAUSL

Remarks : Port Size
 IN Port • G1/8 male thread
 OUT Port • G1/8 female thread



Small-Size Pulse Blow Unit PAU-05

Order Codes

PAUL - 05 - ☐

Port Size

Code : IN Port

- M5** : M5 female thread
J4 : ϕ 4mm [0.157 in.] One-touch fitting
J6 : ϕ 6mm [0.236 in.] One-touch fitting
01A : Rc1/8
01B : R1/8
01C : G1/8 male thread

OUT Port

- M5 female thread
 M5 female thread
 Rc1/8
 Rc1/8
 Rc1/8
 G1/8 female thread

Remarks :

A mounting bracket is not supplied.
 When the product is to be fixed in place, prepare a suitable mounting bracket separately.

《Recommended Mounting Bracket》

- Akagi Co., Ltd. Resin Band (Light Gray)
 CLIC Standard Model No. A10530-0284



Pulse Blow Unit PAU Series

Order Codes

PAUL - ☐ - ☐

Mounting Type

- Blank** : Mounting holes only
21 : Mounting bracket included

Port Size

Code : IN Port

- Blank** : Rc1/4
02 : Rc1/4
F11 : NPT1/4 female thread
F21 : G1/4 female thread

OUT Port

- G1/4 female thread
 Rc1/4
 NPT1/4 female thread
 G1/4 female thread



Pulse Blow Unit PAU-30 Series

Order Codes

PAUL - 30 - ☐ - ☐ - ☐

Thread Type

- Blank** : Rc
F11 : NPT female thread
F21 : G female thread

Port Size

- 02** : 1/4 (IN/OUT)
03 : 3/8 (IN/OUT)

Mounting Type

- Blank** : Without mounting holes
25 : Direct Mounting



Pulse Blow Unit PAU-50 Series

Order Codes

PAUL - 50 - ☐ - ☐

Mounting Type

- Blank** : Mounting holes only
25 : Direct Mounting

Port Size

- 04** : Rc1/2 (IN/OUT)
06 : Rc3/4 (IN/OUT)

